

DATA SHEET LINEAR FLUSHED LED LAMPS SERIES



Power led lamps with forced heat reduction for special applications

- Structure made by single chamber extruded polycarbonate
- Terminals made by neutral anodized aluminium with double O-Ring for sealing
- IP 65 Rated
- Fast insert connections for heat reduction fluid tube, 6 mm diameter
- Power supply bipolar cable with free ending or with M8 connector
- Colour temperatures available 3500K, 4000K, 5700K
- Incorporated 350mA driver for Flushed 260 and 700mA for Flushed 500
- Power supply +24 Vdc
- Room temperature (check specifications on Data-sheet)
- ATEX classified locations use (check specifications on Data-sheet)
- Compliance with EN 62471:2008-09 group 1
- CE Marking

Model	Dimensions (mm)	Maximum power (W)	Lux at		
			100cm	160cm	220cm
FLU026xxxxxxx	260 x Ø 42	4,9	585	153	78
FLU050xxxxxxx	500 x Ø 42	12,25	990	262	145

For further information please ask us the complete product Data-Sheet

STARDUST★

IS A PRODUCT LINE UNDER THE OWNERSHIP OF BOSTON ELETTRONICA S.R.L.
VIALE ORTLES, 80 - 20139 MILANO ☎ 02/55211283