

**DATA SHEET ROUND FLUSHED LED LAMPS SERIES**




**Power led lamps with forced heat reduction for special applications**

- Metal-Core PCB 1,6mm thick
- Heat sink integrated
- Black die-cast aluminium body
- Fast insert connections for heat reduction fluid tube, 6 mm diameter
- INOX steel front panel
- Thick tempered glass with anti-glare diffuser
- IP 65 Rated
- Colour temperatures available 3500K, 4000K, 5700K
- Power supply +24 Vdc constant current with on board 350, 500 or 700mA driver
- Room temperature (check specifications on Data-sheet)
- ATEX classified locations use (check specifications on Data-sheet)
- Average lifetime 50.000 hours
- Tripolar insulated cable 10 cm or 15 cm long for connection with tripolar male M8 connector or tripolar insulated cable 500 cm long with free endings
- Compliance with EN 62471:2008-09 group 1
- CE Marking

Model	Lux at				
	50cm	100cm	150cm	200cm	250cm
<b>FLU110N0700xxx</b>	700	195	95	55	35
WHITE LED 5700K with 700mA driver					

➤ Dimensions

- Inox front panel diameter: 110 mm
- Inox front panel thickness: 3,5 mm
- Led lamp maximum diameter: 97 mm
- Insertion hole recommended diameter: 100 mm
- Minimum depth for recess: 150 mm connections included



**For further information please ask us the complete product Data-Sheet**

**STARDUST** <sup>☆</sup>

IS A PRODUCT LINE UNDER THE OWNERSHIP OF BOSTON ELETTRONICA S.R.L.  
VIALE ORTLES, 80 - 20139 MILANO ☎ 02/55211283