

**DATA SHEET LINEAR LN06 LED LAMPS SERIES**



**Power LED double light lamp for surface supporting installation**

- PCB made with Metal-Core standard (1,6mm) and high thickness (3mm)
- Double series 10 + 10 power led on board
- White LEDs colour temperatures available 3500K, 4000K, 5700K
- Available LED colours Royal Blue – Blue – Green – Yellow – Orange - Red
- Costant current power supply with 350mA, 500mA, 700mA on board driver
- Room temperature 25°C
- Average lifetime 50.000 hours
- Connection with tripolar insulated cable 10 cm or 50 cm long with M8 male connector or tripolar insulated cable 50 cm long with free endings
- Compliance with EN 62471:2008-09 group 1
- CE Marking

Model	Dimensions (mm)	Lux emanated at				
		50cm	100cm	150cm	200cm	250cm
<b>LN065WNxxxxxxx<sup>1</sup></b>	550 x 14 x 3	1830	570	275	170	110
<b>LN065xxAMxxxxx<sup>2</sup></b>	550 x 14 x 3	1540	460	230	140	90
<sup>1</sup> 4000K WHITE LED <sup>2</sup> 590nm YELLOW LED						

- Coloured LED typical wavelenght

Royal blue	460 nm	Blue	475 nm
Green	530 nm	Amber Yellow	590 nm
Orange	615 nm	Red	625 nm

**For further information please ask us the complete product Data-Sheet**

**STARDUST** *☆*

IS A PRODUCT LINE UNDER THE OWNERSHIP OF BOSTON ELETTRONICA S.R.L.  
VIALE ORTLES, 80 - 20139 MILANO ☎ 02/55211283