

DATA SHEET LINEAR LN18 LED LAMPS SERIES**Middle power led lamps for free-standing installation**

- Extruded neutral anodized aluminium structure
- End cover in grey technopolymer
- Available colors: 3500K white, 4000K white, 5700K white, red, amber yellow, green, blue
- Typical CRI coefficient: 80
- Constant current power supply, 2000mA Max - 24 Vdc, with DVBK series Boston driver
- Ambient temperature 25°C
- Average life 40.000 hours
- Output available: 10 cm or 50 cm bipolar cable with tripolar M8 male connector or free wires, 10 cm or 70 cm red/black bipolar flat cable with fast plug connector.
- Compliance to IEC/TR 62778:2014 group 0, photobiological safety
- CE conformity

Model	Dimensions (mm)	Max power (W)	Lux at		
			70cm	90cm	130cm
LN1801	316 x 19 x 11.5	7	820	500	250
LN1802	616 x 19 x 11.5	13	1500	930	460
LN1803	906 x 19 x 11.5	20	1970	1280	670
LN1804	1206 x 19 x 11.5	27	2250	1550	850
LN1805	1506 x 19 x 11.5	34	2450	1760	1040
LN 1806	1806 x 19 x 11.5	40	2580	1900	1165

For further information ask for the product complete datasheet

STARDUST ☆

is a product line propriety of BOSTON ELETTRONICA S.R.L.