

DATA SHEET LINEAR LN20 LED LAMPS SERIES**Middle power led lamps for free-standing installation with 45° emission angle**

- Extruded neutral anodized aluminium structure
- End cover in transparent technopolymer
- Available colors 3500K white, 4000K white, 5700K white, red, amber yellow, green, blue
- Typical CRI coefficient: 80
- 24 Vdc constant voltage power supply, power consumption from 400mA to 2A according to lamp length
- Ambient temperature 25°C
- Average life 40.000 hours
- Four different types of diffuser
- Output available: 10 cm or 50 cm bipolar cable with tripolar M8 male connector or free wires
- Compliance to IEC/TR 62778:2014 group 0, photobiological safety
- CE conformity

Model	Dimensions (mm)	Max power consumption (mA)	Lux at		
			100cm	150cm	200cm
LN2001	396 x 19.3 x 19.3	400	225	102	55
LN2002	766 x 19.3 x 19.3	800	390	183	115
LN2003	1136 x 19.3 x 19.3	1200	537	278	178
LN2004	1506 x 19.3 x 19.3	1600	751	389	249
LN2005	1876 x 19.3 x 19.3	2000	975	505	323
LN2006	346 x 19.3 x 19.3	400			
LN2007	666 x 19.3 x 19.3	800			
LN2008	976 x 19.3 x 19.3	1200			
LN2009	1296 x 19.3 x 19.3	1600			
LN2010	1606 x 19.3 x 19.3	2000			

For further information ask for the product complete datasheet

STARDUST ☆

is a product line propriety of BOSTON ELETTRONICA S.R.L.