

**DATA SHEET ROUND VEHICLE PROOF LED LAMPS SERIES**




**Power LED lamps for floor installation**

- Metal-Core PCB 1,6mm thick
- Integrated heatsink
- Black die-cast aluminium body
- ABS back structure
- INOX steel front panel
- Thick tempered glass with anti-glare diffuser
- IP 65 Rated
- Colour temperatures available for white led 3500K, 4000K, 5700K
- +24 Vdc constant current power supply with on board 350, 500 or 700mA driver
- Room temperature 25°C
- Average lifetime 50.000 hours
- Tripolar insulated cable 10 cm or 15 cm long for connection with tripolar male M8 connector or tripolar insulated cable 500 cm long with free endings
- Compliance with EN 62471:2008-09 group 1
- CE Marking

Model	Maximum Power (W)	Lux at				
		50cm	100cm	150cm	200cm	250cm
<b>RN110N0700</b>	8	700	195	95	55	35
WHITE LED 5700K with 700mA driver						

➤ Dimensions

- Inox front panel diameter: 110mm
- Led lamp diameter: 80mm
- Insertion hole diameter for led lamp back structure housing: 100mm
- Minimum depth for recess: 140mm



**For further information please ask us the complete product Data-Sheet**

**STARDUST** ☆

IS A PRODUCT LINE UNDER THE OWNERSHIP OF BOSTON ELETTRONICA S.R.L.  
VIALE ORTLES, 80 - 20139 MILANO ☎ 02/55211283