

**DATA SHEET TUBE BICOLOR LED LAMPS SERIES**



**Middle power high brightness led lamps, IP65 rated, semi-recess installation**

- Structure made by single chamber extruded polycarbonate available in 5 different lengths with transparent, opaline or transparent with glazed diffuser finishing.
- Terminals made by neutral anodized aluminium with double O-Ring for sealing and directable fixing hole.
- IP 65 Rated.
- Power supply cable connection made with nichel-plated brass.
- On board tripolar terminal block for +24 Vdc power supply and 0:10V regulation bus connection or tripolar cable 10 cm or 50cm long with M8 male connector.
- Double led series for two-tone management with single led lamp (it's not possible light up at the same time the two different led series).
- Colour temperatures available for white led 3500K, 4000K, 5700K
- Led colours available, Red, Amber Yellow, Green, Blue.
- On-board driver available with 350mA, 500mA, 750mA, 1050mA, 1400mA, 1580mA currents.
- Room temperature 25° C.
- Compliance with EN 62471:2008-09 group 0.
- CE Marking.

Model	Dimensions (mm)	Led number	Max power (W)
<b>TB040xxxxxxxxxx</b>	410 x Ø 46 max	2X18	11
<b>TB050xxxxxxxxxx</b>	550 x Ø 46 max	2X27	16
<b>TB065xxxxxxxxxx</b>	690 x Ø 46 max	2X36	22
<b>TB080xxxxxxxxxx</b>	830 x Ø 46 max	2X45	27
<b>TB095xxxxxxxxxx</b>	970 x Ø 46 max	2X54	33

**For further information please ask us the complete product Data-Sheet**

**STARDUST** ☆

IS A PRODUCT LINE UNDER THE OWNERSHIP OF BOSTON ELETTRONICA S.R.L.